

Pump for Standard Barrel of DEF with 19mm Nozzle



1. Set up pump with 19 mm nozzle connected and 5 feet or more of compatible hose.
2. Can be used pneumatically with BGA shop air adapter.
3. Fluid flow at 4 gpm.

MODEL #GT200DEF-5	INCLUDES: Pump, nozzle, 5-ft. hose
MODEL #GT200DEF-20	INCLUDES: Pump, nozzle, 20-ft. hose
MODEL #DEFNOZZLE-5	INCLUDES: nozzle, barb connection, 5-ft. hose
MODEL #DEFNOZZLE-20	INCLUDES: nozzle, barb connection, 20-ft. hose

Pump for MicroMatic Barrel of DEF with 19mm Nozzle



1. Includes 4 pin MicroMatic fitting, adapter, 19mm DEF nozzle.
2. Add 5 to 20 feet of compatible hose.
3. For IBC Totes, use with BGA specialty Pneumatic Adapter for Totes.
4. Fluid flow at 4 gpm.

MODEL #GT200DEF-MM-5	INCLUDES: Pump, nozzle, 5-ft. hose
MODEL #GT200DEF-MM-20	INCLUDES: Pump, nozzle, 20-ft. hose
MODEL #DEFNOZZLE-5	INCLUDES: nozzle, barb connection, 5-ft. hose
MODEL #DEFNOZZLE-20	INCLUDES: nozzle, barb connection, 20-ft. hose

Hose Dry-Break and Swivel Connections



Dry break connections for the hose allow easy disassembly at any point along the hose, most typically near the pump.



Stainless steel swivel connection is ideal at the nozzle end.

MODEL #DRYBREAK-DEF	INCLUDES: Male and Female Barbed Pair
MODEL #DEF-SS SWIVEL	INCLUDES: Stainless Steel hose Swivel

BGA Pneumatic Adapter and Air Filter



The BGA pneumatic adapter allows continuous availability of liquids without recharging the container by hand. Features a regulator with a low-volume air pressure gauge and automatic external pressure relief at 4 psi. For IBC totes, please specify required IBC-BGA specialty adapter.



The F3512-400 with 5 micron element is recommended for use with the BGA due to the high purity requirements for DEF.

MODEL #BGA	INCLUDES: Regulator, 4 psig external pressure relief
MODEL #BGA-IBC	INCLUDES: Regulator, 2 psig external pressure relief
MODEL #F3512-400	INCLUDES: 5 micron air filter, all connections